



PROWLER PRO S





BLANK CANVAS. ENDLESS OPPORTUNITIES.

A limited-edition twist on Arctic Cat's top workhorse, the Prowler Pro S is primed for customization. With all the features that set the Prowler Pro apart, such as the 50-horsepower engine, 12.5 inches of ground clearance, and performance tuned CVTech clutch, this vehicle is a blank slate to make your own. The Prowler Pro S offers a customizable experience for wherever the trails take you, and with a 6-seat Crew option available, you'll have room for the whole crew.

KEY FEATURES

- Built to Accessorize:
 - Pre-Installed Wiring for Accessories
 - Standard 75-Amp Alternator
 - Formed ROPS for Easy Installation of Cab Components and Clean Fit and Finish
 - Over 50 Custom-Built Accessory Options Available
- 800-Class, 3 Cylinder Engine Tuned for Low Noise, Smooth Operation, and Optimal Power Delivery
- 2,000 lb. Towing Capacity and 1000 lb. Bed Capacity
- Standard Electronic Power Steering (EPS)
- Trail-Tuned Suspension with 12.5-in. Ground Clearance
- Removeable Passenger Seats with Behind Seat Storage
- Toolless Service Components with Easy Access Panels

ENGINE & DRIVETRAIN ENGINE TYPE Liquid-Cooled, 3-Cytinder DISPLACEMENT B12cc DRIVETRAIN CVT DRIVE SYSTEM 2WD / 4WD Electric Actuation with Selectable Rear Diff Lock FUEL SYSTEM Electronic Fuel Injection (EFI) GEAR SELECTION H/L/N/R/P FRONT DIFFERENTIAL 2WD / 4WD Open REAR DIFFERENTIAL Selectable Locking STEERING EPS FRONT SUSPENSION Double A-Arm with 10-in. 125.4-cm) Travel BRAKE SYSTEM 4 Wheel Hydrautic Disc, Dual Piston Caliper Front, Single Piston Caliper Rear PARKING BRAKE Park in Transmission FRONT TIRES 26x9-14 REAR TIRES 26x9-14 REAR TIRES 26x9-14 REAR TIRES 26x9-14 REAR TIRES 26x11-14 WHEELS Aluminum PERFORMANCE TOTAL CAPACITY 1,500 lbs. (680.4 kg) BED CAPACITY 2,000 lbs. (907.2 kg) DIMENSIONS OVERALL LENGTH 126 in. (320 cm) 161 in. (408.9 cm) OVERALL HEIGHT OVERALL WIGHT 177 in. (195.6 cm) OVERALL HEIGHT OVERALL WIGHT 1585 lbs. WHEELBASE 85 in (215.5 cm) 118.5 in. (301 cm)		PROWLER PRO S	PROWLER PRO CREW S	
DISPLACEMENT 812cc DRIVETRAIN CVT DRIVE SYSTEM 2WD / 4WD Electric Actuation with Selectable Rear Diff Lock FUEL SYSTEM Electronic Fuel Injection (EFI) GEAR SELECTION H/L/N/R/P FRONT DIFFERENTIAL 2WD / 4WD Open REAR DIFFERENTIAL Selectable Locking STEERING & SUSPENSION STEERING & EPS FRONT SUSPENSION Double A-Arm with 10-in. [25.4-cm] Travel REAR SUSPENSION Double A-Arm with 9.5-in. [24-cm] Travel BRAKE SYSTEM 4 Wheel Hydraulic Disc, Dual Piston Caliper Front, Single Piston Caliper Rear PARKING BRAKE Park In Transmission FRONT TIRES 26x9-14 REAR TIRES 26x11-14 WHEELS Aluminum PERFORMANCE TOTAL CAPACITY 1,500 lbs. (680.4 kg) BED CAPACITY 1,500 lbs. (690.4 kg) BED CAPACITY 1,000 lbs. (453.6 kg) DIMENSIONS OVERALL LENGTH 126 in. (320 cm) 161 in. (408.9 cm) OVERALL WIGHT 1585 lbs. 1856 lbs.	ENGINE & DRIVETRAIN			
DRIVETRAIN CYT	ENGINE TYPE	Liquid-Cooled, 3-Cylinder		
DRIVE SYSTEM 2WD / 4WD Electric Actuation with Selectable Rear Diff Lock FUEL SYSTEM Electronic Fuel Injection [EFI] GEAR SELECTION H/L/N/R/P FRONT DIFFERENTIAL 2WD / 4WD Open REAR DIFFERENTIAL Selectable Locking STEERING & SUSPENSION STEERING FRONT SUSPENSION Double A-Arm with 10-in. (25.4-cm) Travel REAR SUSPENSION Double A-Arm with 9.5-in. (24-cm) Travel BRAKE SYSTEM 4 Wheel Hydraulic Disc, Dual Piston Caliper Front, Single Piston Caliper Rear PARKING BRAKE Park In Transmission FRONT TIRES 26x9-14 REAR TIRES 26x9-14 WHEELS Aluminum PERFORMANCE TOTAL CAPACITY 1,500 lbs. (680.4 kg) BED CAPACITY 1,000 lbs. (453.6 kg) TOWING CAPACITY 2,000 lbs. (907.2 kg) DIMENSIONS OVERALL LENGTH 126 in. (320 cm) 161 in. (408.9 cm) OVERALL WIDTH 63 in. (160 cm) OVERALL WIGHT 1585 lbs. 1856 lbs.	DISPLACEMENT	812cc		
FUEL SYSTEM Electronic Fuel Injection (EFI)	DRIVETRAIN	CVT		
GEAR SELECTION H/L/N/R/P FRONT DIFFERENTIAL 2WD / 4WD 0pen REAR DIFFERENTIAL Selectable Locking STEERING & SUSPENSION STEERING FRONT SUSPENSION Double A-Arm with 10-in. [25.4-cm] Travel REAR SUSPENSION Double A-Arm with 9.5-in. [24-cm] Travel BRAKE SYSTEM 4 Wheel Hydraulic Disc, Dual Piston Caliper Front, Single Piston Caliper Rear PARKING BRAKE Park In Transmission FRONT TIRES 26x9-14 REAR TIRES 26x11-14 WHEELS Aluminum PERFORMANCE TOTAL CAPACITY 1,500 lbs. [680.4 kg] BED CAPACITY 1,500 lbs. [680.4 kg] BED CAPACITY 2,000 lbs. [907.2 kg] DIMENSIONS OVERALL LENGTH 126 in. [320 cm] 161 in. [408.9 cm] OVERALL WIDTH 63 in. [160 cm] OVERALL HEIGHT 77 in. [175.6 cm] OVERALL WEIGHT 1585 lbs. 1856 lbs.	DRIVE SYSTEM	2WD / 4WD Electric Actuation with Selectable Rear Diff Lock		
FRONT DIFFERENTIAL 2WD / 4WD Open	FUEL SYSTEM	Electronic Fuel Injection (EFI)		
STEERING & SUSPENSION STEERING & SUSPENSION STEERING EPS FRONT SUSPENSION Double A-Arm with 10-in. (25.4-cm) Travel REAR SUSPENSION Double A-Arm with 9.5-in. (24-cm) Travel BRAKE SYSTEM 4 Wheel Hydraulic Disc, Dual Piston Caliper Front, Single Piston Caliper Rear PARKING BRAKE Park In Transmission FRONT TIRES 26x9-14 REAR TIRES 4 Wheels WHEELS Aluminum PERFORMANCE TOTAL CAPACITY 1,500 lbs. (680.4 kg) BED CAPACITY 1,000 lbs. (453.6 kg) TOWING CAPACITY 2,000 lbs. (907.2 kg) DIMENSIONS OVERALL LENGTH 126 in. (320 cm) 161 in. (408.9 cm) OVERALL WIDTH 63 in. (160 cm) OVERALL HEIGHT 77 in. (175.6 cm) OVERALL WEIGHT 1585 lbs. 1856 lbs.	GEAR SELECTION	H/L/N/R/P		
### STEERING & SUSPENSION ### STEERING	FRONT DIFFERENTIAL	2WD / 4V	VD Open	
STEERING EPS FRONT SUSPENSION Double A-Arm with 10-in. (25.4-cm) Travel REAR SUSPENSION Double A-Arm with 9.5-in. (24-cm) Travel BRAKE SYSTEM 4 Wheel Hydraulic Disc, Dual Piston Caliper Front, Single Piston Caliper Rear PARKING BRAKE Park In Transmission FRONT TIRES 26x9-14 REAR TIRES 36x11-14 WHEELS Aluminum PERFORMANCE TOTAL CAPACITY 1,500 lbs. (680.4 kg) BED CAPACITY 1,000 lbs. (453.6 kg) TOWING CAPACITY 2,000 lbs. (907.2 kg) DIMENSIONS OVERALL LENGTH 126 in. (320 cm) 161 in. (408.9 cm) OVERALL WIDTH 63 in. (160 cm) OVERALL HEIGHT 77 in. (175.6 cm) OVERALL WEIGHT 1585 lbs. 1856 lbs.	REAR DIFFERENTIAL	Selectable Locking		
FRONT SUSPENSION Double A-Arm with 10-in. (25.4-cm) Travel REAR SUSPENSION Double A-Arm with 9.5-in. (24-cm) Travel BRAKE SYSTEM 4 Wheel Hydraulic Disc, Dual Piston Caliper Front, Single Piston Caliper Rear PARKING BRAKE Park In Transmission FRONT TIRES 26x9-14 REAR TIRES 36x11-14 WHEELS Aluminum PERFORMANCE TOTAL CAPACITY 1,500 lbs. (680.4 kg) BED CAPACITY 1,000 lbs. (453.6 kg) TOWING CAPACITY 2,000 lbs. (907.2 kg) DIMENSIONS OVERALL LENGTH 126 in. (320 cm) 161 in. (408.9 cm) OVERALL WIDTH 63 in. (160 cm) OVERALL HEIGHT 77 in. (195.6 cm) OVERALL WEIGHT 1585 lbs. 1856 lbs.	STEERING & SUSPENSION	N		
REAR SUSPENSION Double A-Arm with 9.5-in. [24-cm] Travel BRAKE SYSTEM 4 Wheel Hydraulic Disc, Dual Piston Caliper Front, Single Piston Caliper Rear PARKING BRAKE Park In Transmission FRONT TIRES 26x9-14 REAR TIRES 26x11-14 WHEELS Aluminum PERFORMANCE TOTAL CAPACITY 1,500 lbs. [680.4 kg] BED CAPACITY 1,000 lbs. [453.6 kg] TOWING CAPACITY 2,000 lbs. [907.2 kg] DIMENSIONS OVERALL LENGTH 126 in. [320 cm] 161 in. [408.9 cm] OVERALL WIDTH 63 in. [160 cm] OVERALL HEIGHT 77 in. [175.6 cm] OVERALL WEIGHT 1585 lbs. 1856 lbs.	STEERING	EPS		
BRAKE SYSTEM 4 Wheel Hydraulic Disc, Dual Piston Caliper Front, Single Piston Caliper Rear PARKING BRAKE Park In Transmission FRONT TIRES 26x9-14 REAR TIRES 26x11-14 WHEELS Aluminum PERFORMANCE TOTAL CAPACITY 1,500 lbs. (680.4 kg) BED CAPACITY 1,000 lbs. (453.6 kg) TOWING CAPACITY 2,000 lbs. (907.2 kg) DIMENSIONS OVERALL LENGTH 126 in. (320 cm) 161 in. (408.9 cm) OVERALL WIDTH 63 in. (160 cm) OVERALL HEIGHT 77 in. (175.6 cm) OVERALL WEIGHT 1585 lbs. 1856 lbs.	FRONT SUSPENSION	Double A-Arm with 10-in. (25.4-cm) Travel		
PARKING BRAKE Park In Transmission FRONT TIRES 26x9-14 REAR TIRES 26x11-14 WHEELS Aluminum PERFORMANCE TOTAL CAPACITY 1,500 lbs. (680.4 kg) BED CAPACITY 1,000 lbs. (453.6 kg) TOWING CAPACITY 2,000 lbs. (907.2 kg) DIMENSIONS OVERALL LENGTH 126 in. (320 cm) 161 in. (408.9 cm) OVERALL WIDTH 63 in. (160 cm) OVERALL HEIGHT 77 in. (195.6 cm) OVERALL WEIGHT 1585 lbs. 1856 lbs.	REAR SUSPENSION	Double A-Arm with 9.5-in. [24-cm] Travel		
FRONT TIRES 26x9-14 REAR TIRES 26x11-14 WHEELS PERFORMANCE TOTAL CAPACITY BED CAPACITY 1,500 lbs. (680.4 kg) BED CAPACITY 1,000 lbs. (453.6 kg) TOWING CAPACITY DIMENSIONS OVERALL LENGTH 126 in. (320 cm) 161 in. (408.9 cm) OVERALL WIDTH 63 in. (160 cm) OVERALL HEIGHT 77 in. (195.6 cm) OVERALL WEIGHT 1585 lbs. 1856 lbs.	BRAKE SYSTEM	4 Wheel Hydraulic Disc, Dual Piston Caliper Front, Single Piston Caliper Rear		
REAR TIRES 26x11-14 WHEELS Aluminum PERFORMANCE TOTAL CAPACITY BED CAPACITY 1,500 lbs. (453.6 kg) BED CAPACITY TOWING CAPACITY 2,000 lbs. (907.2 kg) DIMENSIONS OVERALL LENGTH 126 in. (320 cm) 161 in. (408.9 cm) OVERALL WIDTH 63 in. (160 cm) OVERALL HEIGHT 77 in. (1∀5.6 cm) OVERALL WEIGHT 1585 lbs. 1856 lbs.	PARKING BRAKE	Park In Transmission		
MHEELS Aluminum PERFORMANCE TOTAL CAPACITY 1,500 lbs. (680.4 kg) BED CAPACITY 1,000 lbs. (453.6 kg) TOWING CAPACITY 2,000 lbs. (907.2 kg) DIMENSIONS OVERALL LENGTH 126 in. (320 cm) 161 in. (408.9 cm) OVERALL WIDTH 63 in. (160 cm) OVERALL HEIGHT 77 in. (195.6 cm) OVERALL WEIGHT 1585 lbs. 1856 lbs.	FRONT TIRES			
PERFORMANCE	REAR TIRES	26x11-14		
TOTAL CAPACITY 1,500 lbs. (680.4 kg) BED CAPACITY 1,000 lbs. (453.6 kg) TOWING CAPACITY 2,000 lbs. (907.2 kg) DIMENSIONS OVERALL LENGTH 126 in. (320 cm) 161 in. (408.9 cm) OVERALL WIDTH 63 in. (160 cm) OVERALL HEIGHT 77 in. (175.6 cm) OVERALL WEIGHT 1585 lbs. 1856 lbs.	WHEELS	Aluminum		
BED CAPACITY 1,000 lbs. [453.6 kg] TOWING CAPACITY 2,000 lbs. [907.2 kg] DIMENSIONS OVERALL LENGTH 126 in. [320 cm] 161 in. [408.9 cm] OVERALL WIDTH 63 in. [160 cm] OVERALL HEIGHT 77 in. [175.6 cm] OVERALL WEIGHT 1585 lbs. 1856 lbs.	PERFORMANCE			
TOWING CAPACITY 2,000 lbs. [907.2 kg] DIMENSIONS OVERALL LENGTH 126 in. [320 cm] 161 in. [408.9 cm] OVERALL WIDTH 63 in. [160 cm] OVERALL HEIGHT 77 in. [195.6 cm] OVERALL WEIGHT 1585 lbs. 1856 lbs.		1,500 lbs. (680.4 kg)		
DIMENSIONS OVERALL LENGTH 126 in. (320 cm) 161 in. (408.9 cm) OVERALL WIDTH 63 in. (160 cm) OVERALL HEIGHT 77 in. (195.6 cm) OVERALL WEIGHT 1585 lbs. 1856 lbs.		-		
OVERALL LENGTH 126 in. (320 cm) 161 in. (408.9 cm) OVERALL WIDTH 63 in. (160 cm) OVERALL HEIGHT 77 in. (195.6 cm) OVERALL WEIGHT 1585 lbs. 1856 lbs.		2,000 lbs. [907.2 kg]		
OVERALL WIDTH 63 in. [160 cm] OVERALL HEIGHT 77 in. [195.6 cm] OVERALL WEIGHT 1585 lbs. 1856 lbs.				
OVERALL HEIGHT 77 in. [195.6 cm] OVERALL WEIGHT 1585 lbs. 1856 lbs.		.== (=== =)		
OVERALL WEIGHT 1585 lbs. 1856 lbs.				
WHEELBASE 85 in (215.9 cm) 118.5 in. 1301 cml				
GROUND CLEARANCE 12.5 in (31.75 cm)		12:5 iii (31.7.9 tili)		
·		Standard 2-in Receiver		
		Standard 2-III receiver		
COLOR OPTIONS STANDARD COLORS Fire Red or Marsh Green		Fire Red or Marsh Green		
FEATURES		THE RES OF MULTIPOPER		
		Full Length		
		Multifunctional Digital Gauge		
		·		
LIGHTING Dual High/Low Beam Halogen Headlights with LED Tail Lights	LIGHTING	Dual High/Low Beam Halogen Headlights with LED Tail Lights		
START METHOD Electric Start	START METHOD			
SEATING Bench Seat, 3-Passenger with Removable Passenger Seats, 3 Point Seat Belts Bench Seat, 6-Passenger with Removable Passenger Seats, 3 Point Seat Belts Seats, 3 Point Seat Belts	SEATING		Bench Seat, 6-Passenger with Removable Passenger Seats, 3 Point Seat Belts	
STORAGE Cargo Dump Bed, Glove Box, Behind-Seat Storage	STORAGE			
ADDITIONAL FEATURES Standard Doors	ADDITIONAL FEATURES	Standard Doors		
WARRANTY 18 Months	WARRANTY	18 Months		









